

TEHNIČNI PODATKI

**KOHLER**



Modello	Continui		Emergenza		Motore	N° Cilindri	Potenza Hp/kW	Cilindrata lt	Consumo lt/hr					
	[KVA]	[KW]	[KVA]	[KW]						lt	Kg	mm	lt	mm
CGM 5DE	5	4	5,5	4,4	15LD 350	1	6,3/4,7	349	1	4,3/10	80	750x500x630h	160	1200x690x840h
CGM 7DE	7	5,6	7,7	6,1	15LD 440	1	9,2/6,8	442	1,5	4,5/10	110	900x600x700h	200	1200x690x840h
CGM 10DE	10	8	11	8,8	25LD 330/2	2	11,7/8,6	654	2	4/10	135	900x600x700h	230	1200x690x840h
CGM 12,5DE	12,5	10	13,75	11	25LD 425/2	2	14,5/10,5	851	2,8	4/10	170	900x600x750h	235	1200x690x840h
CGM 15DE	15	12	16,5	13,2	12LD 477/2	2	19/14	954	3,2	7/50	190	1100x650x800h	360	1450x800x1150h
CGM 22DE	22	17,6	24,2	19,4	9LD 625/2	2	26/19	1248	4,2	10/50	245	1100x650x800h	365	1450x800x1150h

TEHNIČNI PODATKI

**KOHLER**



Modello	Continui		Emergenza		Motore	N° Cilindri	Potenza Hp/kW	Cilindrata lt	Consumo lt/hr					
	[KVA]	[KW]	[KVA]	[KW]						lt	Kg	mm	lt	mm
CGM 10DW	10	8	11	8,8	LDW 702	2	15,1/11	686	2,9	50	240	1400x700x850h	290	1600x700x1050h
CGM 15DW	15	12	16,5	13,2	LDW 1003	3	22,4/16,5	1028	3,8	50	300	1400x700x850h	350	1600x700x1050h
CGM 20DW	20	16	22	17,6	LDW 1404	4	29,9/22	1372	5,8	50	320	1400x700x850h	380	1600x700x1050h
CGM 25DW	25	20	27,5	22	LDW 1603	3	36,3/26,7	1649	6,6	50	410	1400x700x850h	460	1600x700x1050h
CGM 30DW	30	24	33	26,4	LDW 2204	4	47,6/35	2199	8	50	430	1400x700x900h	500	1600x700x1050h